

Air Operated Oil Pumps

1735R



Air Operated Stub Style Oil Pump 1:1 Ratio

Includes:

Single Action

Delivery Rate 6 Gallons Per Minute

Air Filter with Automatic Drain

Foot Valve and Screen

½" x 48" Oil Hose

¼" x 48" Air Hose

Male and Female Quick Connects for Air

1700R



3:1 Ratio Pneumatic Pump For oil based fluids and antifreeze

Diamond Selection (5 Year Warranty)

Stub Style

Single Action

Delivery Rate 3.7 GPM

Includes Foot Valve, Air Filter,

Oil Hose, Connecting Hose,

Bung Adapter, Needle Valve,

Male and Female Quick Connects

1730R



5:1 Ratio Pneumatic Pump for Oil, Gear Oil, ATF, and Antifreeze

Diamond Selection (5 Year Warranty)

Stub Style

Double Action

Delivery Rate 4.7 GPM

Includes Foot Valve, Air Filter,

Oil Hose, Connecting Hose,

Bung Adapter, Needle Valve,

Male and Female Quick Connects

Air Operated Grease Pumps

3574R



50:1 Grease Pump. For dispensing from 25 to 50 lb. open head drums of grease.

Features:

Durable chrome finish pump

Air motor with silicon lube to eliminate the need for an oiler

Includes air line filters with auto drain for moisture release

Powder coated drum cover (13 3/4 I.D)

Pump tube is 1 3/16" diameter and 16" long

Follower plate with rubber wiper and dual O-ring seal for the pump shaft

Booster control handle 1536A

Z swivel 1545

1220R



50:1 Ratio Chassis Lube System. Includes pump, control handle, drum cover, follower plate, air filter, Z swivel, and drum dolly.

1212R



65:1 Grease pump system. Includes pump, drum cover, follower plate, air line filter, needle valve, and quick connects. Used to dispense grease from 400-lb. Open head drum.

Manual Oil Pumps

Model 381



Barrel Pump - fits 15 through 55-gallon drums with 2" bung opening. Has a zinc die-cast piston with two brass rings, steel telescoping tube assembly, Buna N Seals, plastic handle grip, and curved discharge spout with garden hose threads. Dispenses approximately 1 pint per stroke. Has adjusting nut on bung threads.

Model 382



Barrel Pump- Same as Model 381 except is equipped with non-drip attachment.

Model 321



Lube Pump - fits full open head pails 5 through 6 ½ gallons. Includes pump, pail cover, and 4 feet of clear vinyl hose with curved discharge nozzle. Can be furnished with MODEL 1500 universal pint meter by special order at additional cost.

Manual Oil Pumps

Model 336



Lube Pump - fits 120 lb. full open head drums. Includes pump, drum cover, and 5' of clear vinyl hose with curved discharge nozzle.

Model 338



Transfer Pump - fits 15 through 55-gallon drums. Dispensing rate of 2 ounces per stroke. Includes pump, bung adapter, and discharge spout with garden hose threads.

FR31



Quart stroke measurement fits in 2" opening for bulk container.

Grease Manual Pumps

Model 550



Grease Pump - hand operated grease pump for full open head pails up to 6-½ gallon size. Includes pump, cover, plastic handgrip, carrying handle, follower plate, 6-foot high-pressure hose, and MODEL 28 coupler.

Model 567



Hand grease pump for 25-50 lb. pails. Spring loaded with booster control handle and follower plate.

Model 540



Hand pump for dispensing grease from 25 to 50-lb pails. Includes 22-lb fully enclosed container. Heavy duty cast iron construction. Includes spring loaded follower plate. Easy to carry handle.

Electric Lubrication Pumps

L5116



Rugged half horse-powered oil transfer pump that measure antifreeze, non-flammable oil-based solvents, waste oil, and hydraulic fluid. This GPI oil transfer pump has a one year warranty.

FR400 Series



13 GPM. ¼ horsepower motor for ethylene glycol, diesel, fuel, grease, hydraulic oil, motor oil, and water. 110 volt or 12 volt.

Model 912-19



Part 912-19 19.2-volt Cordless Grease Gun For delivery of grease in a variety of applications and hard to reach areas

Features:

- 8500 PSI rated 2 Ni-cad batteries
- Whip Hose with spring guard
- Holds 14 1/2-oz. cartridge
- 2 1500mAh battery packs
- Battery charger (1-hr. charging cycle)
- Multiple loading options (cartridge, suction or bulk)
- Hard plastic storage case

Mechanical Preset Meters

Model 1519



Quart Meter. Preset 1 to 16 quarts. Totalizes in U.S. quarts. Automatically shuts off at pre-selected quantity. Includes MODEL 1101 swivel connector and MODEL 1340 automatic non-drip rigid nozzle for motor oils.

Model 1520



Quart Meter. Preset 1 to 60 U.S. quarts. Totalizes in U.S. gallons. Automatically shuts off at pre-selected quantity. Includes MODEL 1101 swivel

Digital Preset Meters

Model 1517



Digital preset meter for dispensing in pints, quarts, liters, or gallons. Totalizes in gallons or liters. Automatic nozzle with non-drip tip. Safety lock to prevent accidental operation. Cover and trigger are impact resistant plastic. 2 AAA batteries.

Model 1522



Digital preset meter for dispensing in pints, quarts, liters, or gallons. Totalizes in liters or gallons. Factory programmed and calibrated. ½" pipe extension with automatic non-drip attachment. 4 AA Batteries.

Digital Meters

Model 1504



Digital meter for dispensing in pints, quarts, liters and gallons. Large, easy to read 5-digit display. Equipped with extension hose, automatic non-drip nozzle, control handle, and rubber shroud. Easily replaceable 3 volt lithium battery.

Model 1509



Digital meter for dispensing in pints, quarts, liters, or gallons. Totalizes in gallons or liters. Cast aluminum housing. Easily replaceable 3 Volt lithium battery.

Model 1510



Digital meter for dispensing in pints, quarts, liters, or gallons. Totalizes in gallons or liters. Safety lock to prevent accidental operation. Cover and trigger are impact resistant plastic. 2 AAA batteries.

Mechanical Meters

Model 1515



Quart Meter - U.S. quarts with ¼-quart graduations. Totalizes in U.S. quarts. Includes MODEL 1101 swivel connector and MODEL 1315 non-drip flexible nozzle for motor oils and ATF.

Model 1508



Quart Meter - U.S. quarts with ¼-quart graduations. Totalizes in U.S. quarts. Includes MODEL 1101 swivel connector and MODEL 1340 automatic non-drip rigid nozzle for motor oils.

Model 1525



Zee Line Mechanical Meter The "Ease of Use" standard in the lubrication market
Easy to read dial
One button reset
Odometer style display
Dispenses up to 8 gallons per minute
Includes automatic non-drip tip
Includes 12 inch flexible hose
Rugged handle with trigger guard
Oval gear meter for optimum accuracy
4-digit resettable totalizer
6-digit accumulative totalizer
Shock resistant
No battery required

Oil Control Handles

Model 1587



Low-Pressure Control Valve. Same as MODEL 1581 except has flexible hose in place of steel pipe.

Model 1575



Deluxe Oil Control Handle. Includes MODEL 1576 with MODEL 1315 flexible hose MODEL 26 non-drip tip.

Model 1572R



Oil control handle for transferring oils and antifreeze. Includes trigger lock. 1/2" NPT fitting. Outlet diameter 13/16".

Grease Control Handles

Model 1534



Continuous Flow Handle

Features:

Pressure is determined by the pump used with this handle

Continuous flow

Steel construction

1/4" NPT inlet

1/8" NPT outlet

Grease coupler (28)

Available options:

"Z" swivel

1/4" F NPT Inlet

1/4" M NPT outlet (1547)

Model 1533



Booster Handle with Pressure Relief Valve

Features:

Each pull of the handle increases pressure to a maximum

10,000 PSI

Steel construction

1/8" NPT inlet/outlet

Equipped with a pressure relief valve to allow for easy removal of grease coupler

Model 1536A



Booster Handle

Features:

Each pull of the handle increases pressure to a maximum

10,000 PSI

Aluminum construction

1/8" NPT inlet

1/8" NPT outlet

Grease coupler (28)

Available options :

"Z" swivel

1/4" F NPT inlet

1/8" M NPT outlet (1545)

Lubrication Reels

Model 1440R



Heavy-duty for stationary and mobile truck mounting

Features:

Steel construction with heavy-duty base

Dual arm support

3-position guide for ceiling, wall or bench mounting

Adjustable hose stop

Drum support bushing with self lubricating material

Easy and safe replacement of spring can

Durable red powder-coated finish

¼" x 52 ft. hose

Maximum pressure 5000 PSI

Model 1444R



Heavy-duty for stationary and mobile truck mounting

Features:

Steel construction with heavy-duty base

Dual arm support

3-position guide for ceiling, wall, or bench mounting

Adjustable hose stop

Drum support bushing with self lubricating material

Easy and safe replacement of spring can

Durable red powder-coated finish

½" x 49 ft. hose

Maximum pressure 2500 PSI

Model 1458R



Heavy-duty for stationary and mobile truck mounting

Features:

Steel construction with heavy-duty base

Dual arm support

3-position guide for ceiling, wall, or bench mounting

Adjustable hose stop

Drum support bushing with self lubricating material

Easy and safe replacement of spring can

Durable red powder-coated finish

3/8" x 59 ft. hose

Maximum pressure 300 PSI

Oil Bars

Model 1610R



Oil Bar with single tap. Anti-splash filter on tap. Easy to clean removable drip tray.

Model 1608R



Heavy non-drip self closing oil bar spigot.

Model 1505



Pint Meter - U.S. quarts with $\frac{1}{4}$ -quart graduations. With totalizer. Totalizes in U.S. quarts. Inlet and outlet $\frac{1}{2}$ " NPT (Female).

Premium Lever Style Pumps

Model 1208



Gear Lube Pump - fits 120 lb. open head drums. Includes pump, drum cover, 5' (longer hoses not recommended) of medium pressure oil hose, non-drip curved discharge nozzle, MODEL 1500 universal pint meter, and MODEL 120-S drum dolly.

Model 1209



Gear Lube Pump - Fits 120 lb. open head drum. Includes drum cover, 5 ft. (longer hoses not recommended) of medium pressure oil hose, non-drip curved discharge nozzle, drum dolly.

Model 366



Barrel Pump w/o hose - fits 15 through 55-gallon drums with 2" bung opening. Has zinc die-cast piston with brass piston ring. Includes bung adapter and curved discharge spout. Discharge spout can be rotated 180° and can be removed to expose garden hose threaded outlet. Dispenses approximately 1-1/2 pints per stroke.

Waste Oil Drains

Model 1235



Adjustable Waste Oil Drain. 17 Gallon Capacity.

Model 318



18 Gallon Oil Lift Drain. Translucent red polyethylene container for view of oil level. Pour spout and hand grips on top and bottom with spout and 3/4" evacuation valve. Height adjusts and is on ball bearing wheels.

Model 237



Low Boy Oil Drain with evacuation kit. Heavy duty polyethylene with wire screen. Translucent body for view of fluid level. 17 gallons. Four lubricated casters recessed into body.

Grease Guns

Model 613



Zinc Plated Grease Gun

Features:

Maximum pressure 5000-PSI

Delivers 1 oz. per 40 strokes

Holds 14 ½ oz. cartridge

Hydraulic coupler (P/N 27SP)

Zinc plated barrel

Multiple loading via cartridge, suction or bulk

Comfortable one-hand operation

Cast steel head

12" whip hose included

Model 911



Single Shot Air operated pistol grip grease gun. 40:1 pressure ratio. Maximum pressure 4,000 PSI. 75 to 100 psi inlet pressure. Delivers .60 oz. per 40 strokes. Heavy duty aluminum die cast head with bulk loader valve. Internal bore precision honed for rapid action. Single shot operation.

Model HD4A



Grease Gun - a heavy duty lever style gun. Maximum pressure 10,000 PSI. with either short or long strokes. Includes heavy-duty coupler, 12" whip hose, and MODEL 80 loader nipple. Can be filled by standard 14-½ ounce cartridge or gun filler pump.