



ENERGY STORAGE SOLUTION

STORAGE SYSTEM

PRODUCT MODEL

- BW-INV-SPH3.6K
- BW-INV-SPB5K
- BW-INV-SPH5K
- BW-BAT-10.1P



HIGH PERFORMANCE

- 200% PV over management;
- 200% backup overload capacity, 60A battery current;
- Max. efficiency 97.3%, Battery efficiency 97%;
- Load monitoring accuracy 10W, Battery discharging threshold 10W;



HIGH RELIABILITY

- UPS level redundant protection against backup load breakdown;
- Three-level firmware and two-level hardware battery protection;
- Multiple temperature monitoring, delicate thermal management;
- Max. 6 Inverters in parallel to increase power availability.



HIGH INTELLIGENCE

- Internal EMS optimizes home energy supply automatically;
- PV production forecast;
- Built-in electric power service, FCAS, VPP, etc.;
- Online monitoring, online diagnosis, online service.

INVERTER MODEL	BW-INV-SPH3.6K	BW-INV-SPB5K	BW-INV-SPH5K
PV INPUT			
Max. PV Input Power Max.	7.36kW		10kW
PV Input Voltage	580V		580V
MPPT Range	100~550V		100~550V
Max. Input Current	15A/15A		15A/15A
Max. Short Circuit Current	18.75A/18.75A		18.75A/18.75A
MPP Trackers	2		2
Strings Per MPP Trackers	1/1		1/1
AC PORT			
Rated Grid Output Power	3.68kVA	5kVA/4.6kVA(DE)	5kVA/4.6kVA(DE)
Max. Grid Input Power	7.36kVA	10kVA	10kVA
Rated Grid / Backup Voltage		230Vac	
Rated Grid/ Backup Frequency		50/60Hz	
Max. Backup Power	7.36kVA/7.36kW	10kVA/10kW	10kVA/10kW
THDi		<3%	
THDv		<3% (Linear Load) / <5%(Non-linear Load)	
DCV		<100mV	
Crest Ratio		3:1	
Transfer Time		<10ms	
EFFICIENCY			
Max. Efficiency	97.3%		97.3%
Round Trip Efficiency	90%	90%	90%
GENERAL DATA			
Operating Temperature Range		-20~60℃	
Topology		Transformerless	
Dimensions (W*H*D)		590×405×205×205mm	
Weight	19.5kg	18kg	19.5kg
Load Monitoring		Meter / CT / Backup box	
External Communication		RS-485 / WIFI / 4G / Ethernet	
Grid Regulation		CEI 0-21,VDE 4105-AR-N,VDE 0126-1-1,EN 50438,G99,G100,AS4777.2 NRS 097,EN 50549,C10/C11,UNE,UTE,NCRfG/PTiREE	
Safety Regulation		IEC 62109-1&2,IEC 62477	
BATTERY MODEL		BW-BAT-10.1P	
Battery Type		LFP	
Battery Capacity		10.1kWh	
Usable Capacity		9.6kWh	
Depth of Discharge (DoD)		95%	
Nominal Battery Voltage		96V	
Operating Voltage Range		90~108V	
Max.Charging Current		52.5A	
Max. Discharging Current		52.5A	
Operating Temperature Range		-10~50℃	
Cycle Lifetime		8000	
Parallel		1~6	
Dimensions (W*H*D)		590×750×205mm	
Weight		90kg	
Communication		CAN / RS-485 (Optional)	
Safety Regulation		IEC 62619, IEC 62040	
Transportation		UN3803	
SYSTEM			
Operating Altitude		≤4000m	
Relative Humidity		0~95% (No Condensing)	
Protection Degree		IP65	
Cooling		Nature Convection	
Noise		<30dB	
Warranty		5 years / 10 years (optional)	
EMC		EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4	

Note: Specifications are subject to change without advance notice.